
DATASHEET TEMPERATURE SENSOR



94085



Benefits

The SSTS-94085 temperature sensor is a sturdy design, has proven sealing concepts, fast response times and they are 100% tested in production.

Applications

These sensors are compatible with a wide range of coolant, motor oil, fuel and liquid applications.

ELECTRICAL AND MOUNTING SPECIFICATIONS

Nominal Resistance	2.055 Ohm (25°C), 186.5 Ohm (100°C)*
Temperature Range	-40°C to 150°C
Time of Response	T63 < 15s (water)
Thread	M14x1.5
Connector	Bosch Compact (D928, 002, 69A)
Sealing Ring	Al-seal, captive
Protection Range	IP6K9K
Product Code	94085

^{*}Other resistant values on request

1/	V /	۵ ۱	N	IN	١G
v	v /	٩г	N۱	H I	v

Personal Injury

DO NOT USE these products as safety or

Emergengy Stop devices or in any other application Where failure of the product could result in

Personal injury.

Failure to comply with these instructions could

Result in death or serious injury.

CAUTION

Do not exceed maximum ratings.

Although the sensor is protected against supply reversal, it is not recommended.

Do not overtighten screw-in type.

Do not use chlorinated solvents.

Do not mount with dome pointing downwards.

Failure to comply with these instructions may result in product damage.

It is the customer's responsibility to ensure that this product is suitable for use in their application. For techincal assistance or advice, please email us: info@sstsensing.com